

Symbol DS6700 Series

Handheld digital imager scanner



FEATURES

1.3 Megapixel imaging

Provides resolution to support image capture and bar code scanning; provides flexibility to capture documents as large as 8.5 in. x 11 in./21.6cm x 279cm

Support for all major 1D, PDF, postal and 2D symbologies

Delivers application flexibility; eliminates need for multiple devices — and associated costs

RSM (Remote Scanner Management) Ready

Lowers IT expenses and TCO by enabling remote management from a central location

Text enhancement technology

Ensures legibility of text in scanned documents

6 ft./1.8m drop specification,

tempered glass exit window Designed to endure the rigors of everyday use for maximum reliability and uptimes; reduces downtime and TCO

Capture data and images with single multi-use device

The versatile Symbol DS6700 Series from Motorola delivers the functionality of a 1D and 2D bar code scanner, digital camera and document scanner in a single device. Designed to meet a wide variety of business needs across a variety of industries, the Symbol DS6700 enhances employee productivity and streamlines business processes in retail, government, manufacturing and more by combining an onboard 1.3 megapixel camera with high performance scanning features and superior digital imaging technology.

Enhance employee productivity

The Symbol DS6700 Series delivers the accurate and rapid first time scanning of bar codes required to maximize employee productivity. Whether you need to read 1D, 2D or PDF417 bar codes, the Symbol DS6700 Series provides true point-and-shoot bar code capture — there is no need to orient products to the scanner window, and a viewfinder ensures the image is properly captured the first time. Users can dynamically switch between hands-free and handheld operation to quickly, easily and safely scan large items. And a pick list function expands

usability from the front room to the back room, enabling rapid processing of orders and more.

Superior document clarity for record-keeping applications

Our text enhancement software delivers the document clarity required to streamline record-keeping, replacing paper-based files with electronic filing. From medication prescriptions to bills of lading, the high-resolution camera and text-enhancing software work hand-inhand to ensure the visibility of text on documents captured, including very small print. As a result, critical business information is literally at your fingertips, helping to reduce administrative and regulatory compliance costs.

An outstanding return on investment

The Symbol DS6700 Series reduces capital and operating expenses by eliminating the need to purchase, manage and support additional devices — such as digital cameras and separate bar code scanners for different symbologies. Fewer devices to deploy significantly reduces the time and costs associated with training — and positively impacts productivity. The ability to remotely track, deploy and upgrade Symbol DS6700 Series scanners reduces

SYMBOL DS6700 SERIES Handheld digital imager scanner

Multiple on-board interfaces; universal cable compatible

Easy to install; futureproof — today's cradle can connect to tomorrow's host

360° omni-directional scanning; wide working range, laser aiming pattern

Easy to use; no need to align item and scanner; virtually no training required

Optional hands-free Intellistand

Enables presentation scanning and automatic switching between hands-free and handheld modes typical management costs. And since even the most intelligent devices require a support plan, Motorola's Service from the Start Advance Exchange Support agreement provides next-business-day delivery of a replacement device for maximum uptime and true service peace of mind.

For more information on how the Symbol DS6700 series can give your enterprise a business advantage, visit www.motorola.com/ds6700 or access our global contact directory at www.motorola.com/enterprisemobility/contactus

Symbol DS6700 Series Specifications

Dimensions:	6.55 in. H x 4.72 in. L x 2.82 in. \		
	16.6 cm H x 11.9 cm L x 7.1 cm W		
Weight:	6.4 oz. (182 g)		
Voltage and Current:	5 +/-10%VDC @ 350 mA		
Color:	Cash Register White (shown) or	Twilight Black	
Performance Character	istics		
Light Source:	Aiming: 650 nm laser diode Illumination: 630 nm LED		
Field of View: (Vertical x Horizontal)	SR - Standard range: 34° V x 43° H DC - Document capture: 35° V x 44° H		
Roll / Pitch / Yaw:	SR - Standard range: 360°, ±65°, ±60° DC - Document capture: 360°, ±65°, ±60°		
Symbology Decode Cap	ability		
1-D:	UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII, Tri-optic Code 39, RSS variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code 93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5, MSI, Codell, IATA, Bookland EAN, Code 32		
PDF417 (and Variants):	PDF417, microPDF417 and composite codes		
Postal:	U.S. Postnet and Planet, U.K., Japan, Australian, and Dutch		
2-D:	MaxiCode, DataMatrix (ECC 200), QR Code and Aztec		
Print Contrast:	25% minimum reflectance		
Motion Tolerances:	Horizontal velocity: 5 in. (12.7 cm) per second		
Interfaces Supported:	DS6707: RS-232C (Standard, Nixdorf, ICL, and Fujitsu) USB (Standard, IBM SurePOS, Macintosh) and Synapsi connectivity allows for connectivity to all of the above plus many non-standard interfaces. DS6708: Includes above plus IBM 468x/469x and keyboard wedge		
	s (NDC) can be encoded in various grammed to parse these codes us		
Imaging Characteristic	s (DS6707 ONLY)		
Image (Pixels):	1.3 Megapixel: 1280 pixels H x 1024 pixels V		
Graphics Format Support:	Images can be exported as Bitm	ap, Jpeg, and Tiff	
Image Transfer Speed:	USB 1.1: Up to 12 Megabits/second RS232: Up to 115 kb baud rate		
Image Transfer Time:	Typical USB application is ~ 0.2 seconds with a compressed Jpeg of 100 kb		
Imaging Distance: (Vertical x Horizontal)	Document Sizes:	Minimum Distance (Approximate)	
	2 1/8 x 3 3/8 in. (5.4 x 8.6 cm)	2.4 in. (6.1 cm)	
	4 x 6 in. (10.2 x 15.2 cm)	5.7 in. (14.5 cm)	
	5 x 7 in. (12.7 x 17.8 cm)	6.9 in. (17.5 cm)	
	8 x 11 in. (21.6 x 28 cm)	11.9 in. (30.2 cm)	
	Ranges are from the nose of the	ceanner and are hace	

"Note: Imaging characteristics only apply	to the DS6/U/. The DS6/U8 does not
support image transfer.	

User Environment		
Sealing:	IP41 (Water and Dust Resistant)	
Operating Temperature:	32° to 122° F / 0° to 50° C	
Storage Temperature:	-40° to 158° F / -40° to 70° C	
Humidity:	5% to 95%, non-condensing	
Drop Specifications:	Withstands multiple 6 ft. (1.8m) drops to concrete	
Ambient Light Immunity:	Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting.	
Regulatory		
Electrical Safety:	UL6950-1, CSA C22.2 No. 60950-1, EN60950-1 / IEC60950-1	
Laser Safety:	EN60825-1:1994 +A1: 2002 +A2: 2001, IEC60825-1, 21CFR1040.10 and 21CFR1040.11, CDRH Class II, IEC Class 2	
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, CISPR 22, CISPR 24; Medical electrical equipment: EN60601-1-2: 2002	
Environmental:	Compliant with RoHS directive 2002/95/EEC	
Mounting Options (Accessories):	Intellistand with adjustable height: 5–10 in. (12.7–25.4 cm) and adjustable angle: 0°–90° Desktop and wall-mount holders are also available.	
Power Supplies:	Power supplies are available for applications that don't supply power over the host cable.	
Mannantu	·	

Warran

Subject to the terms of Motorola's hardware warranty statement, the Symbol DS6707/8 handheld scanner products are warranted against defects in workmanship and materials for a period of five years from the date of shipment. For the complete Motorola hardware product warranty statement, go to: http://www.motorola.com/enterprisemobility/warranty

SR - Standard Range focus

	Depth of Field		
Label Density	DS6700		
Paper Label	English	Metric	
5 mil (Code 39):	1.1 – 6.5 in.	2.8 – 16.5 cm	
13 mil (100% UPC/EAN):	0.5 – 9.7 in.	1.3 – 24.6 cm	
20 mil (Code 39):	0.5 – 15.2 in.	1.3 – 38.6 cm	
PDF417 (10 Mil):	0.9 – 7 in.	2.3 – 17.8 cm	
Datamatrix (10 Mil):	1.1 – 7.5 in.	2.8 – 19.1 cm	

DC - Document Capture focus

	Depth of Field		
Label Density	DS6700		
Paper Label	English	Metric	
5 mil (Code 39):	2.5 – 10 in.	6.5 – 25.4 cm	
13 mil (100% UPC/EAN):	0.8 – 16.8 in.	2 – 42.7 cm	
20 mil (Code 39):	0.7 – 28.3 in.	1.8 – 71 cm	
PDF417 (10 Mil):	1.9 – 11.8 in.	4.8 – 30 cm	
Datamatrix (10 Mil):	2.6 – 12.2 in.	6.6 – 31 cm	



motorola.com



Solutions for Automatic Identification, Barcodes and Mobility

More than 3000 customers in 15 countries • More than 12,000 products in stock



www.logiscenter.com 902 050 030



www.logiscenter.it 02 479 216 97



www.logiscenter.deinfo@logiscenter.de



www.logiscenter.pt 308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the befenits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permament stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



PVC card printers



Barcode readers



RFID



Data terminals & PDA



Consumables (labels, ribbons, PVC cards)

Our Brands









*DATALOGIC



●Metrologic



EPSON®



SEGIT

unitech

PRINTRONIX

<u>symbol</u>*

